

**«Filter-PP»  
Technical Manual**


**Unit Description**..... **2**  
**Unit connection** ..... **2**  
 Табл.1. Unit port outputs assignment. .... 3  
 Табл.2. Technical data and operation conditions ..... 4  
 Табл.3. Standard delivery kit ..... 4

**Unit Description**

Filter-PP (v 2.2) unit (hereinafter referred to as "the unit") is designed for Porsche Panamera, Cayenne (2011--) vehicles. The unit's purpose is to remove the blocking of video feed on the original monitor, which is automatically blocked when the car starts moving.

The unit is connected to the CAN-bus breakage and interfaces with it on hardware and software levels. The unit is fully transparent for both the vehicle and diagnostic equipment and does not interfere with the vehicle electronic equipment operation and original video system control and functioning.

The unit can operate in one of two modes: active (ON) and passive (OFF).

The unit can be activated and deactivated with "return" button  located on the steering wheel, or a specially installed alternative button. Below any of these buttons is mentioned as "controlling button". Original button saves its primary function regardless of the unit operation mode. Unit activation and deactivation is carried out with long pressing of the controlling button (for no less than 2 sec) when the ignition is ON.

Activated unit removes video feed blocking from the original screen without interfering with other equipment's operation.

Deactivated unit retransmits CAN-bus signals without changing them. In the meantime, vehicle equipment operation including the display is carried out in accordance with original algorithms.

Information about unit operation mode is stored in permanent memory and its condition will not change should the power be deactivated.

LED is used for indicating the unit's condition. It can be installed in any area or not installed at all. If the unit is OFF or the ignition is OFF then LED is always OFF. When switching the unit ON the LED turns ON for no less than 4 sec then shuts down. The LED indicates that the unit is ON by lighting with every pressing of control button for the time it is pressed and also by lighting for 4 sec when switching the ignition ON. For all the other cases, the LED is always OFF.

When the CAN-bus switches to hibernation mode, the unit enters the energy saving (standby) mode regardless of whether it is ON or OFF.

It is recommended to switch the unit OFF in case of: putting the car on maintenance in the service station, or when you need to use the standard navigation system and while you do not need to use the unit.

**Unit connection**

The unit is connected in the breakage of the CAN-bus line near the PCM unit's port (see Fig. 1).



Рис. 1

CAN bus is a twisted pair wire composed from orange-brown CAN-L and orange-violet CAN-H wires connected to their corresponding contacts No. 9 and No. 11 of the indicated port. Unit port outputs numbering is shown in Fig. 2.




Рис. 2 Unit port outputs numeration, from the wiring viewpoint.

Output assignment is shown in Table 1.

**Табл.1. Unit port outputs assignment.**

No	Wire Color	Type	Assignment
1	Black	Power supply	«Ground»
2	Brown	CAN 2	CAN-L vehicle data bus
3	Brown	CAN 1	CAN-L vehicle data bus
4	Green/Black	(-) Output	To the blue wire of the LED
5	Green/White	(-) Input	Alternative unit activation/deactivation button
6	-	-	-
7	-	-	-
8	-	-	-
9	-	-	-
10	Red	Power supply	+12V unit supply
11	Brown/Red	CAN 2	CAN-H vehicle data bus
12	Brown/Red	CAN 1	CAN-H vehicle data bus
13	Green	(+) Output	To the red wire of LED
14	-	-	-
15	-	-	-
16	-	-	-
17	-	-	-
18	-	-	-

CAN 1 unit's wire pair is connected with CAN bus from the vehicle's side, while CAN 2 unit's wire pair is connected to the bus from PCM unit's side. Brown wires of the unit are connected with orange-brown wires of the vehicle, while brown-red wires of the unit are connected with orange-violet wires of the vehicle.

The black wire of the unit coming from the contact No. 1 of the unit port is connected to the brown wire of the vehicle coming to contact No. 12 of PCM unit's port (see Fig. 1).

Unit's red wire is connected to the red-yellow wire of the vehicle connected to contact No. 15 of PCM unit port (see Fig. 1).

Green/white wire is connected to vehicle's ground via normally open alternative control button in case when the button installation is necessary.

**Табл.2. Technical data and operation conditions**

Characteristic	Data
Voltage, V	9 ... 15
Max. current in working mode, mA	200
Max. current in standby mode, mA	1,5
Temperature, °C	- 40 ... + 85
Relative humidity, %	95

**Табл.3. Standard delivery kit**

Item	Q-ty
Central unit	1 pc
Cable harness with terminal	1 pc
LED indicator with wiring	1 pc
Technical Manual	1 pc
User memory card	1 pc
Package	1 pc

Product warranty is provided for 1 year since the moment of the sale if all the installation recommendations have been followed. In case of warranty case please contact to the company which sold this product to you.

Distributor \_\_\_\_\_ Date of sale \_\_\_\_\_



**AB75**

Manufacturer «TEC electronics» Ltd.  
 Product is produced according to TY 4372-006-78025716-10.  
 Certificate of origin No POCC RU.AB75.B00340  
 Product corresponds to regulatory documents:  
 ГОСТ P 41.97-99, ГОСТ P 50789-95